Izoterm Plama d.o.o
Save Kovačevića bb
22320 Indija
Srbija
tel: +381 (0)22 510 981
fax: +381 (0)22 510 980
komercijala@izoterm-plama.rs
www.izoterm-plama.rs

Technical Data Sheet

IZOTERM

Plamacell Eco White
Expanded low-density polyethylene foam for laminate flooring

Description
The insulation foil made of closed-celled polyethylene foam with the thickness of 1,5 mm.

Application
Foil Plamacell Eco White can be used for different applications since it is light, flexible and recyclable. It satisfies all the most important criteria for insulation of the laminate floors.

Storage
No exposure to direct sunlight and/or heat. The storage location should also be dry and dust free. Not complying with these precautionary measures can lead to a degradation of the product.

Technical Data:

Basic characteristics	Values and features	Standardised technical specification
Thickness	1,5 mm ± 10%	ISO 1923
Width	1000 mm ± 1,0 %	ISO 1923
Lenght	25 m ± 1,5 %	ISO 1923
Density	20 kg/m^3 ± 10%	ISO 845
Colour	White	-
Material group	Expanded polyethylene	-
Cell structure	Closed-cell structure	-

The product is 100% CFC and HCFC free.

The performance of the ***Foil Plamacell Eco White*** is consistent with the declared properties in this document.
This Technical Data Sheet is commisioned with the sole responsibility of the manufacturer Izoterm-Plama doo.

Certified in accordance with:
Quality management systems ISO 9001:2008,
Environmental management system ISO 14001:2004.

SIQ ISO 9001 Q-1971 ISO 14001 E-567 IQNet